

MILLS DESIGN
 GLENDALE, KILBRIDE, Co. WICKLOW, IRELAND
 PHONE / FAX: +353 404 48500 / 48501
 e-mail: info@mills-design.com



MAT 1180
 for: M.A.T.
 Original Copyright 01/07/2014
 File: MAT 1180 SDP C
 Hull: -1025

COPYRIGHT
 THIS DRAWING FILE MUST NOT BE REPRODUCED, STORED, OR USED FOR ANY PURPOSE
 OTHER THAN AS CONDUCTED BY THE CLIENT OR OTHERS FOR WHICH IT WAS DRAWN,
 WITHOUT THE DESIGNER'S WRITTEN CONSENT.
 THE COST OF THESE PLANS INCLUDES FEES FOR ONE SET ONLY FOR
 PRINTING AND DELIVERY. ALL OTHERS SHALL BE MADE FROM THESE
 PLANS WITHOUT THE DESIGNER'S CONSENT IN THE FORM OF SCHEDULE B TO THE
 CONTRACT AND THE PAYMENT OF APPROPRIATE FEES.

By signing this file
 I agree to the
 terms and
 conditions
 of the
 contract
 of 00

Release	Date	Revision
A	28/04/14	Production release, detail to be added.
B	22/05/14	Increased L2 -50, headstay on stem
C	22/07/14	MC Revised Over Headline

Note to Sailmakers re IRC
 Roke: Sail plan shown at 1.5 deg. Initial roke for
 dock tune of 1.2 deg. = 324mm between main
 halyard and aft face of gooseneck.
 Main Girths: Suggested starting point for small
 fathhead mainsail profile:
 MBG = -21°E
 MLW = -31°E
 MTW = -41°E
 MHW = -51°E
 Jibs: LL rarely approaches FL (start at 90%),
 balance of LL and overline mid-girths should be
 considered when finalising JB sizes, larger for light
 airs.
 J will vary according to mast section chosen.
 Spinnakers: Suggested base spinnaker area SPA:
 160m² asymmetric spinnakers flown from sprit
 Note sprit length STL is related to SPA.
 Sailmakers should be aware of the detail of the
 current IRC Rule, and should contact Designer during
 sail design to discuss these suggestions.

